

Publication—National Ocean Service—U.S. Coast Pilot 8, Alaska: Dixon Entrance to Cape Spencer, 2003 (25th) Edition. Change No. 18.

Coast Pilot 8 25th Ed 2003

Corrections

Page 148-Paragraph 302, line 6; read:
(55°23'41"N., 131°45'53"W.), 24 feet (7.3 m) above the ...
(03/04 CG17; LL/03)

Page 150-Paragraph 321, line 3; read:
bight in the W shore about 1 mile N of the S tip of **Sharp Point** ...
(NOS/04)

Page 165-Paragraph 130, lines 3-4; read:
side. **Tamgas Harbor Entrance Light** (55°01'19"N., 131°30'49"W.), 30 feet (9.1 m) above the water, is shown ...
(03/04 CG17; LL/03)

Page 230-Paragraph 523, lines 18-20; read:
the dredged sections of the channel. In May 2000, the controlling depth was 8.9 feet in the dredged sections of the channel with 3.7 feet in the right outside quarter at Daybeacon 9 and 7.1 feet in the left outside quarter between Daybeacon 3 and Daybeacon 2.
(BPs 171981-996)

Page 244-Paragraph 146, line 4; read:
the latter. A lighted buoy is about 0.2 mile N of the ...
(06/04 CG17)

Page 275-Paragraph 106, line 1; read:
Grave Point Light (58°03'44"N., 134°03'04"W.), 45 ...
(LL/03)